



Certificate of conformity of the factory production control 1071– CPR – 1048

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Huntonit Bygningsplater

Huntonit Proff Vegg

Huntonit Bygningsplater and Huntonit Proff Vegg are medium density wood fiber boards for use in dry conditions with nominal thickness 9 – 11 mm and density $\leq 840 \text{ kg/m}^3$.

placed on the market under the name or trade mark of

Byggma ASA

Postboks 21
4701 Vennesla

and produced in the manufacturing plant(s)

Huntonit AS

Venneslavegen 233
4708 Vennesla

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 13986:2004+A1:2015

under system 2+ are applied and that

the factory production control is assessed to be in conformity with the applicable requirements.

This certificate was first issued on 14.06.2004 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body, and latest until 01.02.2030.

The certificate is valid provided it is listed on www.sintefcertification.no.

Oslo, 26.02.2026

Anne-Jorunn Enstad
Certification Manager



SINTEF

Certificate of conformity of the factory production control

1071– CPR – 1048

Appendix

Product	Property	Standard	Classification
Huntonit Bygningsplater	Board type	EN 622-1:2003, table 1 og 2 EN 622-3: 2004, table 2	MBH
	Reaction to fire	EN 13501-1:2007+A1:2009	D-s1, d0 ¹⁾
Huntonit Proff Vegg	Board type	EN 622-1:2003, table 1 og 2 EN 622-3: 2004, table 2	MBH
	Reaction to fire	EN 13501-1:2018	-

1) The classification is valid for the following end use conditions:

- Any end use substrate of Euroclasses A1 or A2-s1, d0 at least 9 mm thick, having a density ≥ 38 kg/m³
- Mechanically fixed according to the manufacturer's installation instructions. Can be installed with both horizontally and vertically joints.
- Can be installed with and without a void.

Issued: 14.06.2004 | Revised: 26.02.2026 | Valid until: 01.02.2030

SINTEF AS by its institute SINTEF
Community | SINTEF Certification

v250226

Page 2 of 2